80ft Diesel Knuckle Boom

PERFORMANCE*

Platform Height	24.38 m
Working Height	26.38 m
Horizontal Outreach	15.80 m
Up and Over Clearance	9.78 m
Swing	360 Degrees Continuous
Platform Capacity	230 kg
Platform Size	0.91 x 2.44 m
Platform Rotator	180 Degrees Hydraulic
Jib	1.83 m
Jib Range of Articulation	130 Degrees (+70, -60)
Weight	15,560 kg
Drive Speed	4.8 km/h
Gradeability	45%
Turning Radius	
Outside	3.53 m
Inside	1.83 m

STANDARD SPECIFICATIONS*

Power Source

Diesel Engine Fuel Tank Capacity Fuel Consumption

Hydraulic System

Capacity Auxiliary Power

Tyres

Standard

18-625 Foam-Filled

Deutz D2011L04

147.6 L

151.4 L

12V-DC

3.33 L/hr

STANDARD FEATURES*

- 4WD & 4WS
- 180 Degree Hydraulic Platform Rotator
- Platform Console Machine Status
- Light Panel*
- AC Generator including AC Outlets to
- Platform
- 4 Degree Tilt Alarm/Indicator Light
- Swing Out Engine Tray
- 12V-DC Auxiliary Power
- Hourmeter
- Proportional Controls
- * Provides indicator lights at platform control console for system distress, low fuel and foot switch status.

• Control ADE® System

- Horn
- Four-Wheel Hydrostatic Drive
- Oscillating Axle
- Operator Tool Tray Inward Self-Closing Self-Locking
- Swing Gate
- Motion Alarm
- Glow Plugs (Diesel Engines)




- Light Package
- Platform Worklights
- Mesh to Mid-Rail
- Special Hydraulic Oils (Consult Factory)
- Spark Arresting Muffler

Note: Some options may increase lead time, and some option combinations may not be available.

HIRE & SERVICES

BAI



Accessory Packages - SkyWelder® Package

- SkyGlazier[®] Package
- Nite Bright[®] Package
- SkyGuard®
- Cable Ladder Carrier
- ClearSky®

- Pipe Rack

- Lifting/Tie Down Lugs


- Flashing Amber Beacon

80ft Diesel Knuckle Boom



Dimensions

All dimensions are approximate.



Reach Diagram

