

GLOBAL

HIRE & SERVICES



**GLOBAL HIRE
CAIRNS**

**GLOBAL HIRE
TOWNSVILLE**



GLOBAL HIRE TOWNSVILLE

581 Ingham Road
Phone: (07) 4412 1500

GLOBAL HIRE CAIRNS

15 Knight Street
Phone: (07) 4095 4619

SERVICE, SOLUTIONS, SUPPLY

SCISSOR LIFTS

	PRODUCT CODE	PLATFORM HEIGHT (M)	WORKING HEIGHT (M)	LIFT CAPACITY (KG)	DRIVE CAPACITY	OVERALL WIDTH (M)	OVERALL LENGTH (M)	STOWED HEIGHT (M)	STABILIZERS (INDEPENDENT)	GROSS WEIGHT (KG'S)	TYRES	PLATFORM SIZE (M)	EXTENSION DECK (M)	SPECIAL FEATURES
Electric	15'	4.60	6.40	272	2x4	0.76	1.65	1.98	/	1238	Non Marking	1.62 x 0.74	0.90	Compact
	19'	5.80	7.60	227	2x4	0.81	1.68	1.98	/	1503	Non Marking	1.63 x 0.74	0.90	Compact
	20'	6.10	7.90	363	2x4	0.81	2.31	2.00	/	1701	Non Marking	2.29 x 0.76	0.90	Slimline
	26'	7.90	9.80	454	2x4	1.17	2.44	2.25	/	2450	Non Marking	2.03 x 1.07	0.90	Full Height Drive
	32'	9.80	11.60	318	2x4	1.17	2.44	2.40	/	2800	Non Marking	2.13 x 1.14	0.90	Narrow
	33' LE	10.06	11.90	450	2x4	1.75	3.1	2.74	Yes	4930	Non Marking	1.65 x 2.92	0.91	Extension Features
	40' LE	12.20	14.00	360	4x4	1.75	3.1	2.81	Yes	5500	Non Marking	1.65 x 2.92	0.91	Extension Features
Diesel	27'	8.30	10.10	580	4x4	1.77	3.36	2.56	Yes	3450	Solid	2.73 x 1.65	1.20	Self Levelling Outrigger
	32'	9.80	11.80	454	4x4	1.73	2.62	2.50	Yes	4153	Solid	3.20 x 1.80	1.23	Full Height Drive
	3384	10.01	12.10	1134	4x4	2.13	4.88	2.68	Yes	6243	Solid	6.57 x 1.83	*1.52	Full Height Drive, Double Deck
	4390	13.10	14.90	680	4x4	2.29	4.88	2.93	Yes	7192	Solid	6.57 x 1.83	*1.52	Full Height Drive, Double Deck
	5390	16.2	18.00	680	4x4	2.29	4.88	3.15	Yes	8352	Solid	6.57 x 1.83	*1.52	Double Deck

SPECIFICATION

- OnBoard Generators
- 3Kva-8Kva and Air Purifiers available on diesel models
- Mine Spec available
- Extension from both ends

NB. All specifications are approx. only and are subject to manufacturers variance without notice.
Operators should hold a current elevating work platform certificate or competency.

KNUCKLE BOOMS

	PRODUCT CODE	PLATFORM HEIGHT (M)	WORKING HEIGHT (M)	LIFT CAPACITY (KG)	DRIVE CAPACITY	OVERALL WIDTH (M)	OVERALL LENGTH (M)	STOWED HEIGHT (M)	HORIZONTAL REACH (M)	TYRES	GROSS WEIGHT (KG)	GRADEABILITY (%)	UP & OVER HEIGHT
Electric	30'	8.80	10.60	227	2x4	1.20	5.3	2.24	6.30	Non Marking	6630	35	3.8
	34'	10.60	12.40	227	2x4	1.47	5.70	2.00	6.80	Non Marking	5216	20	4.6
	40'	12.20	14.00	227	2x4	1.50	6.70	2.00	6.83	Non Marking	6214	30	6.55
	45'	13.80	15.60	227	2x4	1.80	6.80	2.00	7.60	Non Marking	7557	30	6.9
Diesel	34'	10.60	12.40	227	4x4	1.80	5.70	2.06	6.80	Solid	4854	45	4.6
	45'	13.80	15.60	227	4x4	2.30	6.80	2.10	7.60	Solid	7076	45	6.9
	51'	15.81	17.61	230	4x4	2.34	7.68	2.26	9.48	Solid	7300	45	7.63
	60'	18.30	20.10	227	4x4	2.40	8.88	2.50	13.10	Solid	11200	20	8.5
	80'	24.40	26.10	227	2x4	2.44	11.12	3.00	15.74	Solid	15520	30	9.78
	125'	38.10	39.90	227	4x4	3.81	10.64	3.05	19.25	Solid	20248	45	18.44
	135'	41.10	42.90	272	4x4	2.48	12.90	3.07	21.30	Solid	20366	45	23.0

SPECIFICATION

- OnBoard Generators
- 3Kva-8Kva available on diesel models
- Mine Spec available
- Large and Small Platforms available

NB. All specifications are approx. only and are subject to manufacturers variance without notice.
Operators of boomlift 11 metres and over are required to hold a current workcover accredited certificate.

TELESCOPIC HANDLERS

SPECIFICATION

- Airconditioned
- Includes:
 - 4 in 1 Bucket
 - GP Buckets
 - Certifies Jibs
 - Rotators

MACHINE TYPE	MAX LIFT HEIGHT (M)	MAX LIFT CAPACITY (KG)	GROSS WEIGHT (TONNES)	OVERALL HEIGHT (M)	OVERALL WIDTH (M)	LENGTHS LESS FORKS (M)	MAXIMUM HORIZ. REACH (M) TO LOAD CENTRE	OUTRIGGERS
2506	5.75	2.5	5.12	1.92	1.8	3.75	3.44	No
3007	6.80	3.0	6.00	2.05	2.0	4.65	3.80	No
P28.8L	8.20	2.8	6.04	2.0	2.0	4.25	5.30	No
P30.9	9.20	3.0	7.25	2.47	2.22	4.38	5.92	No
4010	9.7	4.0	10.26	2.45	2.25	5.75	6.0	Yes
3013	12.6	3.0	9.90	2.49	2.33	5.53	8.74	Yes
P38.13	12.6	3.8	8.65	2.44	2.22	5.24	8.60	Yes
4515	13.7	4.5	11.4	2.56	2.33	5.99	9.3	Yes
4017	16.7	4.0	12.68	2.565	2.38	6.31	12.7	Yes
P60.10	9.55	6.0	9.86	2.44	2.24	5.34	5.50	No

BOOM LIFTS

SPECIFICATION

- OnBoard Generators
- 3Kva-8Kva available on diesel models
- Mine Spec available
- All units 4WD
- Large and Small Platforms available

	PRODUCT CODE	PLATFORM HEIGHT (M)	WORKING HEIGHT (M)	LIFT CAPACITY (KG)	OVERALL WIDTH (M)	OVERALL LENGTH (M)	STOWED HEIGHT (M)	HORIZONTAL REACH (M)	TYRES	GROSS WEIGHT (KG)	AXLE EXTENSION	GRADEABILITY (%)	JIB
Electric	60'	18.30	20.10	227	2.44	10.15	2.54	13.20	Non Marking	6895	Zero	30	Yes
Diesel	42'	12.80	14.60	227	2.40	7.20	2.40	10.10	Solid	5773	Zero	47	Yes
	45'	13.70	15.50	227	2.30	8.50	2.50	11.20	Solid	6800	Zero	40	Yes
	46'	14.00	15.80	227	2.40	8.84	2.39	12.40	Solid	7800	Zero	45	Yes
	47'	14.20	16.00	227	2.40	8.15	2.40	11.90	Solid	6040	Zero	41	Yes
	50'	15.40	17.20	227	2.40	7.70	2.40	11.90	Solid	5693	Zero	40	Yes
	54'	16.50	18.30	227	2.27	6.77	2.58	14.00	Solid	6350	Zero	40	Yes
	60'	18.30	20.10	227	2.50	9.40	2.70	15.20	Solid	9900	Zero	40	Yes
	65'	19.80	21.60	227	2.44	9.40	2.74	17.20	Solid	12900	Zero	45	Yes
	66'	20.30	22.30	227	2.50	10.10	2.70	17.10	Solid	13550	Zero	45	Yes
	80'	24.40	26.20	227	2.60	11.80	2.90	21.70	Solid	15141	3.90	25	Yes
	85'	25.90	27.70	227	2.43	12.40	2.80	23.40	Solid	17200	3.00	40	Yes
	86'	26.21	28.00	227	2.49	12.19	3.05	22.86	Solid	16510	Zero	45	Yes
	100'	30.40	32.20	270	2.60	13.60	3.20	20.10	Solid	14969	3.90	25	Yes
	125'	38.15	40.15	227	2.49	14.25	3.07	24.38	Solid	20739	3.35	40	Yes
	126'	38.40	40.20	227	2.60	13.00	3.10	19.20	Solid	18978	3.90	25	Yes
	135'	41.15	42.95	227	2.49	11.86	3.05	24.38	Solid	20300	3.81	45	Yes
	SX-135'	41.15	43.15	300	2.49	19.76	3.05	27.43	Solid	21546	3.94	35	Yes

NB. All specifications are approx. only and are subject to manufacturers variance without notice. Operators of boomlift 11 metres and over are required to hold a current workcover accredited certificate.

VERTICAL LIFTS

PRODUCT CODE	PLATFORM HEIGHT (M)	WORKING HEIGHT (M)	MOTOR TYPE	LIFT CAPACITY (KG)	DRIVE CAPACITY	OVERALL WIDTH (M)	OVERALL LENGTH (M)	STOWED HEIGHT (M)	GROSS WEIGHT (KG)	TYRES	PLATFORM SIZE (M)	EXTENSION DECK (M)	GRADEABILITY (%)	TRAVEL HEIGHT (M)
15'	4.50	6.50	Electric	227	2x4	0.76	1.35	1.71	994	Non Marking	0.88 x 0.75	0.51	30	4.6
20'	6.07	8.07	Electric	159	2x4	0.80	1.35	1.98	1112	Non Marking	0.89 x 0.75	0.51	30	6.07
26'	8.00	10.00	Electric	230	2x4	0.99	2.60	1.99	2440	Non Marking	0.90 x 0.70	N/A	25	8.0